


#2013

Mity Bite Clamp


Use for one or two-directional pulling. Good for confined areas. Grip 2" wide.
3 ton capacity.



#2010

Multi Angle Clamp

Pulls from any direction with a 180° arc. Makes two-way pulling faster and easier. 'Bolt stoppers' hold bolts stationary for easier tightening. Grip 3-¾" wide. 4 ton capacity.



#2012

Multi Angle Clamp II

Cross-hatch tooth pattern holds well with less distortion of metal. Large pull plate is adjustable and reversible for more multi-angle pulls. 4 ton capacity.



#1795

Frame Rack Unibody Clamp Bar holes designed for three

ways of pulling using Shackle and Oval Loop. Grip 8" wide. 5 ton capacity.



#2014

Frame Rack Dyna Mo Clamps

One pair of jaws with 7" draw bar, one side pull bracket, shackle and oval loop. Raised 'ears' to hold bolt in place while tightening. Grip surface 3-34" wide.

5 ton capacity.



#1784

Frame Rack Dyna Mo Clamps

Two pair of jaws with 12" draw bar. Grip surface 9-14" wide.



#1777

Three Way Pull Clamp

Clamp has recessed pockets to hold bolts stationary for easy tightening. Includes oval loop. Grip surface 4" wide. 6 ton capacity.



#1929

Slim Line Sill Hook™

Pull front hinge pillars, center pillar posts, rear hinge sections or any location where you need a broad thin pulling surface. Grip 2-1/2" wide.

2.5 ton capacity



$\textbf{Sill Hook} \\ \\ \mathbb{R}$

For a quick pull almost anywhere. Round opening allows for pulling with a slip hook. Grip 2-1/2" wide. 5 ton capacity.



#1910

Double Eye Chain Hook

Handy chain hook-up pulling plate for making double pulls. Allows for both wide or narrow pulls.





#1920

#1865

Clothespin Chain Lock

Maintain chain tension while adjusting for pulls. Chain locks tight. Designed for use with 3/8" chain.

6 ton capacity.



#1850

Handy Link™

Alters chain length. Use 3/8" chain.

5 ton capacity.



Chain Snugger

Tightens chain when used with a chain locking fork (#1920) on frame racks. 6 ton capacity.




#1840

Handy Hook™

No chain is to long and no hooks needed. Pulling slots can be used with Hole Pull Adapters. Use with 3/8" chain.

5 ton capacity.



Welded Double Clevis

For easy 3/8" chain connection. 10 ton capacity.



#1613

Grab/Slip Combo

For hooking into clamps or pull rings. Fast hook up for any section of 3/8" chain. 9-1/2" length.

7 ton capacity.



#1835

30" Nylon Sling

Protects area where chain may damage structure. Vertical: 2.5 tons, Choke: 2 tons, Basket 5 tons, 3" wide.



#1861

Mo Flex Sling

2" wide x 36" long. Vertical: 5,300 lbs, Choke: 4,200 lbs, Basket 10,600 lbs.



#1612

Safety Cable with Hook

Attach to pull chain and point on vehicle. Keeps chain safe.



#1834

36" Cable Sling

Wraps around pulls. Can be used as a choker. Vertical: 1.5 tons, Choke: 1 ton, Basket 2.5 tons.



Working load limit: 6,600 lbs.

3/8" x 25" chain



Hole Plug & Single Claw Length: 26-1/2" Load limit: 6,600 lbs.



Grab Hook & Single Claw Length 24" Working load limit 6,600 lbs.



Hole Plug & Clevis Hook Length 25-3/4" Working load limit: 6,600 lbs.



Strut Tower Chain For use in correction of strut towers. Attach to existing bolt holes. Use with 1/4" chain. 2 ton capacity.




#1937

#2033

#2032




#1811





#1864



Double Looper Two single claws with triangle. Grabs bumpers or panels. Use with %" chain. 5 ton capacity.




#1812

Deep Hook Jumbo Set 10" throat depth; 15" throat opening. 4 ton capacity.



#2040



#1750

Model Mini-C Clamp

Small, light, versatile.
Minimum of 1-1/2" throat clearance to reach around flanges, cowls, pinch welds and lips. Butts against panels where only narrow bite is available.

5 ton capacity.



#1760

Model Jr. Metal Clamp

1-1/2" wide bite for agressive pulling.

5 ton capacity.



#1851

Twin Pull™


For large gripping areas. Enables use of two clamps side by side for more pull. 6 ton capacity.



#1720

Angle Bite™ Clamp

Self-tightening clamp, gator tooth design. 45° head for hard to pull areas. Grip 2-½" wide. 5-ton capacity.




#1721

A Clamp™

Grips narrow seams and ridges. Use with slide hammer and 1/4" chain only. Grip 1-1/2" wide.

3-ton capacity.




#1722

A Clamp with Pull Ring

Grips narrow seams and ridges. Bolt stoppers hold bolts stationary. Includes pull ring for easy chain hook up that swivels in the direction of the pull. Use with 1/4" chain. Grip 1-½".

3 ton capacity.



#1723

Mini Spring Clamp

For pulling light sheet metal in tight places. Spring loaded for easy opening. Includes oval loop for use with slip hook. Grip $1-\frac{1}{2}$ ".

3 ton capacity.



#1875

Curved Clamp

Get around multi-angle curves and bends. Allows for vertical and horizontal pulling. Grip 7" wide.

5 ton capacity.




#1730

Model B Metal Clamp

Ideal for hard pulls on heavy metal or frame. Grabs 2-1/4" of metal.

6 ton capacity.



#1740

Model C® Metal Clamp


1-1/2" throat clearance. Fits over a flange, frame horn or around a lip to pull from behind. Grip 2" wide.



#1780

Model W® Metal Clamp

Ultra wide gripping surface. Grabs 4-1/4" of metal. 6 ton capacity.




#1742

Dyna-Mo C Clamp

Great for getting over lips or edges. Drop-forged round wedge keeps twist out of chain. Grips 1-1/4".

3 ton capacity.




#1762

Dyna-Mo Jr.™ Clamp

Thin edged nose for getting into hard to reach places. Drop-forged round wedge to keep twist out of chain. Grip 1-1/2" wide.

3 ton capacity.




#1782

Dyna-Mo™ W Clamp

Wide tooth surface (2-1/4") to grab more thin metal without tearing.

3 ton capacity.



#1806

Baby Box™ Clamp

Great for single lip flanges and inside frame horns. Throat clearance of 1-1/2" high. Grip 1-3/4".

5 ton capacity.




#1800

Box™ Clamp

For pulling on box rails with welded-on bumper flanges. Reaches around protruding metal to grip on hard-to-reach surfaces. Grip 2".

4 ton capacity.



#1804

Long Nose™ Clamp

Deeper reach for hard to get areas. Grip 1-3/4". 5 ton capacity.



#1798

Tight Opening Clamp


Perfect for small pick-up frame rails. Reach core support and upper sheet metal areas. Grip 1-1/2".

3 ton capacity.



Panel Puller

Use with slide hammer or pulling post on fender openings, deck lids, door posts and other openings. 3 ton capacity.



#2017

Frame Rack Dyna Mo Clamp

Heavy-duty tooth designed clamp. Add side pull bracket when needed. Grip 3 3/4" wide. 5 ton capacity.





#1624

Hole Plua

Four way anchoring tool allows unlimited body and frame hook-up in existing holes. Fastens directly to a 3/8" chain.


5 ton capacity.



#1625

Mo Plua™

Use in existing holes in frame or unibody. Plugs on two sides to allow easy fit into a narrow internal section of frame rail. Uses 3/8" chain. 5 ton capacity.



Multi Pad Metal

Steel plate spreads the load to prevent damage that would be caused by the chain. 6 ton capacity.



#1855

Chain Spread Bar™

Make pulls around box rails or other ostacles while maintaining the distance between pulling clamps.

5 ton capacity.



#2020

Single Claw Hook

Use as an accessory with draw bars or 3/8" chains. 5" length. 6 ton capacity.




#2030

Double Claw Hook

Use as a chain shortener, connector or double hook. For use with 3/8" chain. 5" length.

6 ton capacity.



#1860

Versa Hook

Pulling device for rocker panels, door & windshield posts. Use as an outer track tie-down to secure vehicles during pulls. Grip 2-1/2" wide. 5 ton capacity.



#1870

Jr. Versa Hook

Designed smaller to access tight areas. 1-3/4" wide hook end. Use with 3/8" chain. 5 ton capacity.



#1775

Frame Rack Jaws


Clamp has recessed pockets to hold bolts stationary for easy tightening. Grip 4" wide. 6 ton capacity.



#1970

2 MA™ Plate

Designed for most foreign and domestic vehicles with MacPherson suspension. Offers unlimited body and frame pulls with a variety of compatible accessories. Can be used on damaged door posts, frame horns, brackets, cowls, or rear axles.



#1890

Pull Ring MA Plates

Pull Ring for the 2 MA Adapter. Plate provides for unlimited body and frame pulls. Recessed pockets to hold bolts stationary for easy, one-handed tightening. 5 ton capacity.




#1971

3 MA™ Plate

Designed for strut towers. Permits fast hook up and pulling in any direction.

5 ton capacity.



Boltless Strut Tower Puller

Easy, fast, reliable method for pulling strut towers. 3 ton capacity



#1826

Mo Nut & Bolt Pack

Commonly used bolts, nuts, washers, and clevis pins. Contains grades 5/8 bolts.



#1931

Mo Hook

Four hole size selections for quick hook-ups in existing frame holes for pulling of damaged frames.

4 ton capacity




#1935

Door Post Puller/Twister

For use on bolt-type hinge pillars. Three positions from which to pull.

2 ton capacity.



Hinge Plate with 3/8" Shackle

Use in existing holes in frame structures or body panels. Comes with 3/8" shackle for angle pulls.

3 ton capacity.



#1815

Mo Down Pulley

Use for straight or down angled pulling. 5" wheel pevents undue chain wear.

5 ton capacity.



#1819

Mo Down Pulley Snap Block Assembly


Perfect for horizontal pulls. 5 ton capacity.



#1817, 1818

Weld-on Pinchweld Bracket (set of 4)

12" brackets for welding to bottom of automobiles without pinchwelds.



#1814

G Clamp

Easier pulling with multiple pulling angles. Throat opening of 4" allows plenty of room to get over, around and behind damage.

4 ton capacity.



#1839

Jumbo G Clamp

Throat opening of 7". Multiple holes allow for various angle pulls.

5 ton capacity.



Four Way Pull Clamp Includes oval loop. Has recessed pockets to hold bolts. Stationary for easy tightening. 4" wide grip. 6 ton capacity.

#1773


Flash ClampsPivoting heads allow for a secure grip on most uneven surfaces. Retaining bolt holds clamps in place.



#1960

Slide Hammer Attachment

Screws on end of slide hammer, attach shackle and connect to any pulling tool to make light pulls.



Many Hole Wide Draw Bar Great for bolting to a frame, unibody rail or other places to

unibody rail or other places to make a secure pull. 14-1/2" long.

3 ton capacity.



#2009

Frame Rack Draw Bar

Great for bolting to a frame, unibody rail or other places to make a secure pull. 14-1/2" long. 3 ton capacity.



Narrow Draw Bar with Claw Hook

Great for bolting to a frame, unibody rail or other places to make a secure pull. 13" long. 3 ton capacity.




#1900

Multi-Purpose Anchor Hook

Use on both unitized and conventional frames for a variety of pulls and anchoring.
4 ton capacity.

#2019

#2002



#1880

Numerous Angle Puller™

Allows pulls from any angle. Insert bolt through a 1/2" hole and pull. Designed for use with 3/8" chain. 4 ton capacity.



#1934

Quick Hook™

Quick hook-up in existing frame holes for pulling of damaged frames.

Four hole sizes: 1-7/8", 1-5/8", 1", 7/8".

4 ton capacity.



#1789

Frame Rack Jaws with **Angle Brackets**

Holds down cars with horizontal pinch welds. Angles can be drilled to fit frame racks, benches, etc. Including two 1/2" shackles. 13" wide.


5 ton capacity. (Set of 4)



#1779

Angle Bracket

Bolt to surface for a 90° straight pull, or use with 3-Way Pull Clamp, pair of Frame Rack Jaws or Frame Rack Unibody Clamp. 6 ton capacity.



#1724

Mini Bite™ with Pull Ring

Designed to get around lips and corners for strong pulls and to pull narrow seams and lips. Use with 1/4" chain. 3 ton capacity.



#1856

Panel Gripper

Flat, wide toothless jaw to grip with no distortion. Right angle to pull is great for lips, hoods, tops and floor pans. 9" long. 3 ton capacity.



#1925

Dyna Mo Corner Clamp

Elimates the need to use two separate clamps. Good for narrow confined areas. 7"

3 ton capacity.




#1930

Track Hook™

Quick tie down for track systems or back anchoring on frame racks. Grip 3".


6 ton capacity.



#1807

Big Mouth™ Clamp

Great where large opening is needed. 1-34" grip. 5 ton capacity.



#1810

Lip Grip™ with Pull Bracket


Multi-purpose clamp for non-slip pulls on any lip. Use as sandwich clamp on quarter panels or floor sections. Side pull bracket adds a 90° angle for two-directional pulling. 2" wide.



#1820

Tac-N-Pull™ Clamp

For hard to hold pulls. Tack weld one of the resuable plates, attach clamp and pull. Break tack weld with grinding cut off wheel or cutting torch. Includes (2) each 3"; 1-1/2" and 1" plates.



#1830

Tac-N-Pull™ Replacement Plates

Contains:

(10) 1" Pull Plates

(5) each 1-1/2" & 3" Pull Plates



#1955, #1956, #1957


Tong Clamps

Pivoting jaws on all tong clamps assures a secure grip across the entire gripping surface.

#1955 Small Jaw, 5.25" opening. 5 ton capacity.

#1956 Hybrid, 6" Opening. 5 ton capacity.

#1957 Large, 6.5" opening. 5 ton capacity.



#1809

Sandwich Clamp™

Designed for use as a standard unibody tie down clamp with versatility for pinch weld and panel pulling. Grip 3" wide. 5 ton capacity.